

**NETWORK COMMUNICATIONS HAVING ENDPOINT  
DEVICE WITH AUTOMATIC CONNECTION TO IPBX**

**Related Patent Documents**

This patent document is related to U.S. Patent Application Serial No. 60/154,093 (8X8S.243P1) and entitled "Voice-Over IP Audio Terminal Processor," filed September 15, 1999, and fully incorporated by reference; and is also related to the following patent documents: U.S. Patent Application Serial No. 60/212,220 (8X8S.246PA), entitled "Communications System Architecture," U.S. Patent Application Serial No. 60/212,221 (8X8S.248PA), entitled "IP Phone Circuit Arrangement and Method," U.S. Patent Application Serial No. 09/597,705 (8X8S.249PA), entitled "Communications Controller and Method Therefor," U.S. Patent Application Serial No. 60/211,993 (8X8S.254PA), entitled "High Availability IP Telephony," U.S. Patent Application Serial No. 60/212,215 (8X8S.255PA), entitled "System Interface Implementation for Hosted iPBX," U.S. Patent Application Serial No. 60/211,992 (8X8S.256PA), entitled "IP Telephony Station Equipment," and U.S. Patent Application Serial No. 60/212,219 (8X8S.257PA), entitled "iPBX Hosting," each of which was filed with the U.S. Patent and Trademark Office on June 16, 2000 and is herein fully incorporated by reference.

**Field of the Invention**

The present invention relates to communication systems, and more particularly, to an internet-type telephony endpoint device and communications methodology therefor.

### **Background of the Invention**

The electronics industry continues to rely upon advances in technology to realize higher-functioning devices at cost-effective prices. For many communication applications, realizing higher-functioning devices in a cost-effective manner requires the creative use of communications channels. Many technologies have been developed that have enhanced communications. Examples include the Internet, facsimile applications, public switched telephone networks (PSTN), wireless telephones, voicemail systems, email systems, paging systems, conferencing systems, electronic calendars and appointment books, electronic address books, and video-image processing systems that communicate video data simultaneously with voice data over a telephones and the Internet. As the popularity of these technologies increases, so does the need to merge and coordinate these technologies in a manner that is convenient and cost-effective for the user.

The above-mentioned technologies have been developed in a relatively isolated manner. Large-scale integration of multiple communications systems has been costly and difficult to achieve and manage. One difficulty stems from the variety of communications channels and data types used for various applications. For example, telephony signals can now be transmitted by methods and systems including traditional publicly-switched telephone networks (PSTN), Internet telephony service providers (ITSP), packet-based systems, digital wireless systems, analog wireless systems, private branch exchanges (PBX), cable systems, T1 systems, integrated service digital network (ISDN), and digital subscriber line (DSL) systems, to name a few. Many telephone systems, particularly for business applications, offer services including voicemail,

facsimile, call forwarding, and other call-controls, but these systems are often costly, difficult to manage, limited in scope, and do not offer integration of various communications methods. In addition to difficulties inherent in coordinating telephony-type communications, the coordination of additional communications, such as text, video, or other data, provides additional challenges.

Widespread acceptance and usage of communication systems and services are largely a function of cost and user convenience. Therefore, widespread acceptance and usage of such technology cannot be forced, even when appropriately addressing the marketing needs and overcoming the exorbitant costs of the mass production equipment.

The scalability of a communications system weighs heavily upon the acceptance of the system. As the face of today's workplace is changing, the ability to provide flexible communications services is becoming increasingly important. Many employees are highly mobile, moving between companies and between jobs within a company. When employees are added, leave or move within the company, the communications systems for those employees must be modified. In addition, many employees work from several locations, such as a base office, home, or a branch office. To accommodate ongoing communications needs, a user-friendly and user-reconfigurable system would be advantageous.

### **Summary of the Invention**

The present invention is directed to a telephony communications arrangement and device implementing an autodiscover feature that enables an endpoint device to automatically establish connection with a desirable server in a web of interconnected

servers. In addition, the ease of use and cost-effectiveness of the present invention enable the use of such communications control and coordination many applications, including small and medium-sized business applications. The present invention is exemplified in a number of implementations and applications, some of which are summarized below.

According to an example embodiment of the present invention, a telephony communications arrangement includes an internet-based private branch exchange with a programmable processor circuit programmed to control a server at the internet-based private branch exchange. The server is adapted to communicate to a remote location over a first communications path using a plurality of packet-based communications and endpoint devices. The packet-based communicating endpoint devices are adapted to communicate with the internet-based private branch exchange over a second communications path which is directly coupled communicatively to the first communications path. The second communications path is also communicatively coupled to the plurality of other packet-based servers. Each packet-communicating endpoint device is configured and arranged to automatically broadcast its identity and establish communication with the internet-based private branch exchange from the plurality of other packet-based servers for establishing packet-based communications between the packet-communicating endpoint device and the internet-based private branch exchange.

According to other aspects of the present invention, one or more of the packet-communicating endpoint devices are adapted to seek one of the internet-based private branch exchanges for establishing a communication link. This seeking mode is implemented in different manners, according to different implementations of the present

invention. For example, one implementation involves the endpoint device being adapted to broadcast its identity in anticipation of a DNS (Directive Name Server) being previously configured to monitor for such broadcasts. In response to detecting this broadcast, the DNS responds with an assignment of the iPBX for the broadcasting endpoint device. The broadcasting endpoint device then commences communication with the assigned iPBX.

In another example implementation, the endpoint device broadcasts its identity and a unique iPBX is configured to monitor for such broadcasts. In response to detecting this broadcast, the iPBX responds by informing the broadcasting endpoint device that all subsequent communication should be directed to this unique iPBX.

Respective variations of the above two specific example implementations include further programming the endpoint device with a security code that is used by the monitoring device to reduce the likelihood that the endpoint device would be improperly assigned by either the broadcast-monitoring DNS or the broadcast-monitoring iPBX.

In another example implementation, the packet-communicating endpoint devices are implemented using a forced "address-search" for identifying the internet-based private branch exchange relative to the plurality of other packet-based servers. In this environment, each of the packet-communicating endpoint devices is pre-programmed with the identification of the DNS for the purpose of submitting to the DNS a request for the appropriate iPBX assignment.

According to another example embodiment of the present invention, each of the packet-communicating endpoint devices is further adapted to store a unique Media Access Call address and is able to communicate the unique Media Access Call address

with the internet-based private branch exchange. Further, each of the packet-communicating endpoint devices may be adapted to store a unique code that identifies the internet-based private branch exchange relative to the plurality of other packet-based servers.

In another example embodiment, each of the packet-communicating endpoint devices is further adapted to execute a program that causes the packet-communicating endpoint device to establish communication based on a set of search rules. For example, the endpoint device for one of the servers that manifests an acceptable routing path to establish packet-based communication. This embodiment may be further modified to define the acceptable routing path in terms of an optimally minimum number of routing connections identified over a predetermined time period during a broadcast effort for establishing connection with the desired iPBX.

The above summary of the present invention is not intended to describe each illustrated embodiment or every implementation of the present invention. The figures and detailed description that follow more particularly exemplify these embodiments.

### **Brief Description of the Drawings**

The invention may be more completely understood in consideration of the following detailed description of various embodiments of the invention in connection with the accompanying drawings, in which:

FIG. 1 is an illustration of a packet-based communications system, according to an example embodiment of the present invention;

FIG. 2 is another illustration of a communications system, according to another example embodiment of the present invention;

FIG. 3 is an illustration of an endpoint communications device, according to another example embodiment of the present invention, communicating with an internet-type private branch exchange; and

FIG. 4 is an illustration of another endpoint communications device, according to another example embodiment of the present invention, communicating with an internet-type private branch exchange.

While the invention is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

### **Detailed Description**

The present invention is believed to be applicable to various types of communications systems, and has been found particularly suited to such systems requiring or benefiting from user-friendly control for processing various telephony communications data types and routing the communications via an Internet protocol (IP) type of network. For example, the present invention has been found to be advantageous when operating in conjunction with an iPBX server of the type characterized in the above-referenced patent documents. While the present invention is not necessarily

limited to such systems, various aspects of the invention may be appreciated through a discussion of various examples using this context.

According to an example embodiment of the present invention, a communications service provider network is adapted to receive, process and deliver communications data of various types using a cost-effective, user-friendly operations platform. The network includes a plurality of communication stations communicatively coupled to one or more communications links. One of the communication stations is adapted to communicate packet-based data to a computer server arrangement communicatively coupled to the communications links. The telephony-controlling computer server can be configured in any of a number of ways including, for example, being adapted to operate with a IP telephony switch by passing and/or redirecting data-carrying messages for uniquely-targeted endpoint devices (*e.g.*, an IP telephone, a display or household appliance). The server and/or IP telephony switch is communicatively coupled to the communications stations (and in certain applications other endpoint devices) through a communications links which couples to a multitude of other server-type communication terminals. One (or multiple ones) of the communication stations is programmed to automatically discover a selected one of many possible servers for establishing a link therewith. This automatic discovery is achieved, for example, by designing (*e.g.*, programming) the endpoint device to respond to activation by automatically broadcasting its identity and programming a DNS or a targeted iPBX to monitor the network for such a broadcast and then assign the broadcasting endpoint device with the identity and any desired related codes for establishing communication between the endpoint device and the targeted

005628560

iPBX. Such an assignment from the DNS can be direct or through another server such as the targeted iPBX.

Also according to the present invention, the above-described autodiscover mode is implemented to permit ease of operation for the user of the IP phone. In a particular example embodiment, for example, the autodiscover protocol is implemented by configuring the server-seeking endpoint device with a unique code that identifies the internet-based private branch exchange relative to the plurality of other packet-based servers. In another example embodiment, the autodiscover mode is implemented by forcing a search for a server having one or more selected characteristics based on a set of rules with which the server-seeking endpoint device is programmed to abide by. In another example embodiment, this mode is achieved using a combination of selectable modes, including for example using one of the above approaches as a default mode and each other mode being selectable by the IP phone user or another personnel responsible for the programming and/or maintaining operation of the IP phone.

FIG. 1 is a specific example communications network operating consistent with the above discussion and according to the present invention, and is useful in obtaining a better appreciation of the present invention. In this system, a telephony communications arrangement includes a number of service providers 20, 22, 24 and 26, with the service provider 26 being adapted as a target internet-based private branch exchange providing communications operations with a target set of endpoint devices and another of the service provides being a DNS for the local Web network. The service provider 26 includes a programmable processor circuit (not shown in FIG. 1) programmed to control the server and internet-based private branch exchange operations; these operations

include communicating to remote locations over a first communications path, such as a conventional telephony path (*e.g.*, ISDN, cable, wireless, POTS), linking the service provider 26 as one of a plurality of possible communication targets for IP interface 30. The WEB, depicted as 32 of FIG. 1, is an example of such a first communications path; other examples include those paths that provide more private or secure communications, such as intranet LAN-type applications and government-defined communication networks.

The IP interface 30 is depicted in this example illustration as providing a communications path to the WEB 32 for various endpoint devices such as internet-protocol (IP) phones 41-44, which are interconnected using a second communications path, such as a LAN or other type, provided within one or more facilities hosting the IP phones 41-44. Any of the internet-protocol phones 41-44 can be implemented with an auto-discover mode for seeking a particular type of server, such as a target iPBX-based server 26. In this context, the target set of endpoint devices for the target iPBX-based server 26 includes at least IP phone 41. In one example specific application embodiment, the interface 30 of FIG. 1 is a circuit implementation available from Netergy Networks, Inc., <sup>such</sup> as characterized in connection with the <sup>first (and other of the)</sup> above-referenced patent documents.

In this auto-discover mode, the IP phone automatically searches for and distinguishes the internet-based private branch exchange 26 from the plurality of other packet-based servers 20, 22 and 24 and, in response, establishes packet-based communications with the targeted server.

Implementing the internet-protocol phone 41 with an auto-discover mode is useful in many regards. For example, should a facility location be assigned with an IP phone 41

for the first time, a communications manager (*e.g.*, MIS personnel or an employee responsible for programming/maintaining the IP phone 41) can configure the IP phone 41 so that each time the IP phone attempts to communicate outside the facility or facilities, it searches for a particular server that is configured to remotely manage various aspects of the IP phone 41, for example, as described in connection with the above-referenced patent documents. In this manner, the user of the IP phone 41 does not have to possess any previous knowledge of the target server's IP address or under which circumstances the user should be connecting to one server versus another server.

In another embodiment, the interface 30 of FIG. 1 is programmed and configured to perform the search tasks, including broadcasting functions for example, for implementing this autodiscover mode on behalf of the IP phone 41.

FIG. 2 is another specific example communications network, also according to the present invention, which illustrates another application and other aspects of the present invention. In this communications environment, a service provider 110 is adapted to control and route communications data for a user premise 120. User premise 120 includes a variety of communications devices including an IP phone 122, computers 124 and 126, and two telephones 132 and 134 coupled to an IP gateway 130. Also shown is an IP appliance 135 adapted with a configuration 136 to seek a particular type of service provider, such as the service provider 110 shown in FIG. 2. Each of the devices is communicatively coupled to the service provider via a router 140 and a communications link 150. The service provider is adapted to send and receive communications data via a router 160 coupled to the communications link 150. The router 160 is coupled to the

Internet, to a server 170 and an IP/PSTN gateway 180. The router 160 is adapted to route communications to either the router 140, the Internet, the server or the gateway 180.

The server 170 is programmed to control the routing of communications data to and from the user premise 120. The programming is accomplished in various manners, depending upon the functions being programmed and the security access level of the programming source. First, individual users at the customer premise can program the server. Each user programs various communications selections, such as those described hereinabove. Inputs from the computers 124 and 126, from the IP telephone 122, or from the telephones 132 and 134 are all used for controlling the server. The computers have a user interface adapted to provide various communications selections to the server. The user interface may include, for example, the graphical user interface described in U.S. Patent Application Serial No. 09/597,704 (8X8S.249PA), filed on June 16, 2000, and entitled "Communications Controller and Method Therefor." Selections are made at the computer interface for controlling communications between the computer and one or more other communications devices. Similarly, the IP telephone 122 and other telephones 132 and 134 are used to input control information, such as via a touch-tone sequence or other control code entry.

In addition to programming the server at the user premise 120, the server may also be programmed at remote locations, such as at a communications device communicatively coupled to the Internet or to the PSTN. As discussed in connection with communications devices located the user premise, various control inputs are provided to the server via the respective connections using remote communications devices. For example, Internet communications devices such as a computer, a wireless

telephone having Internet communications ability or an Internet interface such as a WebTV interface could all be adapted for use in communicating with the server to provide programming information.

For further details regarding manners of implementing the system of FIG. 2, reference may be made to U.S. Patent Application Serial No. 60/212,159 (8X8S.247PA), filed on June 16, 2000, and entitled "Communications Service Provider Network."

FIGs. 3 and 4 respectively show first and second example implementations for the endpoint device 41 of FIG. 1, or for endpoint appliance 135 of FIG. 2. With reference to each of these devices 41 and 135, each of FIGs. 3 and 4 includes the corresponding notation 41' and, for the related iPBX, 26'. It will be appreciated that certain of the elements illustrated in FIGs. 3 and 4 are not required for all possible endpoint or appliance types. For example, an endpoint device that does not receive and process user audio does not require an audio input port and related audio-input processing circuitry.

The endpoint device 41' includes audio I/O ports (not shown) and related processing circuitry 202, implementations of which are discussed for example in connection with U.S. Patent Applications, Serial No. 09/086,434 (8X8S.200PA), filed on May, 28, 1998, and Serial No. 09/392,124 (8X8S.239PA), filed on September 8, 1999, and Serial No. 09/203,311 (8X8S.217PA), filed on December 1, 1998. Various implementations for the user-output and user-input implementations 204 and 206 are well known and can be implemented using various technology including the conventional technology presently available on conventional telephones. The endpoint device 41' also includes a voice-over-IP interface circuit 210, which is used to present internet protocol data from the iPBX 26' to the display 204 and/or to the processing circuitry 202. In the

[illegible]

In another specific implementation, the endpoint device broadcasts its identity and a unique iPBX is configured to monitor for such broadcasts. In response to detecting this

broadcast, the iPBX responds by informing the broadcasting endpoint device that all subsequent communication should be directed to this unique iPBX.

For each of these implementations, either of the endpoint-device implementations shown in FIG. 3 or FIG. 4 can be used. For further details of these implementations, reference may be made to the attached entitled, **Symphony MGCP DNS Call Agent Discovery** (Appendix A), and to **VoIP Terminal Discovery Protocol**, (Appendix B); each being fully incorporated herein by reference.

In yet another specific example implementations, the packet-communicating endpoint devices seek a targeted one of the internet-based private branch exchanges for establishing a communication link based on the previously-assigned unique server code assignment being programmed into the respective endpoint devices, for example, as programmed by the facility MIS manager before installation in the network. At such a time (and also with the previous implementations), the facility MIS manager can also program a security or password code for validation to a responding serving node on the network that might attempt to reassign the server code or otherwise establish communication with the endpoint device. After the endpoint device broadcasts its identity, a monitoring DNS or the target iPBX can respond with specific instructions for communication. The broadcasting endpoint device then commences communication based on the assignment(s) being provided.

While the present invention has been described with reference to several particular example embodiments, those skilled in the art will recognize that many changes may be made to the present invention. For example, other embodiments of the present invention can include a combination of one or more aspects discussed herein or as

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

App K. A

## Symphony MGCP DNS Call Agent Discovery

### Introduction

This document describes how a Symphony MGCP MTA can automatically discover its Call Agent address using DNS. The process is designed to be the same as the H323 Gatekeeper DNS discovery procedure for commonality of provisioning between the two protocols. The bulk of this document is a MGCP specific version of the H323 documentation.

### The SRV resource record query

The first solution uses the fact that the call agent is basically a system service, and the transport address of a named system service can be extracted from DNS by using a query for a new type of DNS Resource Record, called SRV (for "service location record"). Given a domain name, an SRV record query will be made for the transport address of the mgcp service for that domain. The format of the response is the same as for a TXT record query documented below.

This simple solution will soon be standard. The problem is that almost no current DNS client or server implementations support the SRV resource record yet. Unless the DNS client knows about the SRV resource record type, it is not possible for it to pass on queries for this resource record. Until this support becomes widespread, there is a reasonable chance that the SRV query will fail.

### The TXT record query

All current DNS implementations support the TXT resource record. Basically this is some free text that can be returned for each domain name. It is possible to store many TXT resources for a single domain. The standard stipulates that all TXT records will be returned when a query is made for them. The domain name is used to make a DNS TXT query for that domain. The returned resource records are lines of free text, and the terminal will then look for lines in the response of the form:

**mgcp [<ca>@]<domain name>[:<portno>] [<priority>]**

The <ca> field is an optional call agent ID which is separate from the domain name. If this field is missing, then it is assumed to be ca.

The <domain name> field can be either the name of the A-record which contains the call agents IP address, or a raw IP address in dotted form. The domain name need not be fully qualified; if it is not, the subdomain in which the TXT record was found should be appended to it to form the fully qualified A-record name.

The optional [:<portno>] can be used to specify a port number other than the standard mgcp port.

The optional [<priority>] field specifies the order in which the listed call agents should be accessed for discovery queries if there is more than one mgcp TXT record. Lower numbers have higher priority.

White spaces are used as delimiters between mgcp and ca if present or domain name, and between portno and priority. White spaces consist of any number of spaces or tabs.

Examples of valid gatekeeper TXT records:

mgcp agent

mgcp ca@agent.company.com

mgcp agent:1500 3

mgcp 172.11.22.33:1500 2

Since DNS requires a server to return all TXT records associated with a domain name, the client can filter out and process only those records which are useful to it. It also allows DNS to return an ordered list of call agents which can serve as alternatives and back-ups.

Note that the server returned in such a query might be an actual transport address in dotted decimal notation, or it could be an FQDN which itself requires an A-record query in DNS to determine the transport address. The advantage of using an FQDN is the usual hiding of actual IP numbers. The advantage of using IP numbers is that a second DNS query is avoided, thus speeding up this pre-call setup time.

1  
 2  
 3  
 4  
 5  
 6  
 7  
 8  
 9  
 10  
 11  
 12  
 13  
 14  
 15  
 16  
 17  
 18  
 19  
 20  
 21  
 22  
 23  
 24  
 25  
 26  
 27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100  
 101  
 102  
 103  
 104  
 105  
 106  
 107  
 108  
 109  
 110  
 111  
 112  
 113  
 114  
 115  
 116  
 117  
 118  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215  
 216  
 217  
 218  
 219  
 220  
 221  
 222  
 223  
 224  
 225  
 226  
 227  
 228  
 229  
 230  
 231  
 232  
 233  
 234  
 235  
 236  
 237  
 238  
 239  
 240  
 241  
 242  
 243  
 244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286  
 287  
 288  
 289  
 290  
 291  
 292  
 293  
 294  
 295  
 296  
 297  
 298  
 299  
 300  
 301  
 302  
 303  
 304  
 305  
 306  
 307  
 308  
 309  
 310  
 311  
 312  
 313  
 314  
 315  
 316  
 317  
 318  
 319  
 320  
 321  
 322  
 323  
 324  
 325  
 326  
 327  
 328  
 329  
 330  
 331  
 332  
 333  
 334  
 335  
 336  
 337  
 338  
 339  
 340  
 341  
 342  
 343  
 344  
 345  
 346  
 347  
 348  
 349  
 350  
 351  
 352  
 353  
 354  
 355  
 356  
 357  
 358  
 359  
 360  
 361  
 362  
 363  
 364  
 365  
 366  
 367  
 368  
 369  
 370  
 371  
 372  
 373  
 374  
 375  
 376  
 377  
 378  
 379  
 380  
 381  
 382  
 383  
 384  
 385  
 386  
 387  
 388  
 389  
 390  
 391  
 392  
 393  
 394  
 395  
 396  
 397  
 398  
 399  
 400  
 401  
 402  
 403  
 404  
 405  
 406  
 407  
 408  
 409  
 410  
 411  
 412  
 413  
 414  
 415  
 416  
 417  
 418  
 419  
 420  
 421  
 422  
 423  
 424  
 425  
 426  
 427  
 428  
 429  
 430  
 431  
 432  
 433  
 434  
 435  
 436  
 437  
 438  
 439  
 440  
 441  
 442  
 443  
 444  
 445  
 446  
 447  
 448  
 449  
 450  
 451  
 452  
 453  
 454  
 455  
 456  
 457  
 458  
 459  
 460  
 461  
 462  
 463  
 464  
 465  
 466  
 467  
 468  
 469  
 470  
 471  
 472  
 473  
 474  
 475  
 476  
 477  
 478  
 479  
 480  
 481  
 482  
 483  
 484  
 485  
 486  
 487  
 488  
 489  
 490  
 491  
 492  
 493  
 494  
 495  
 496  
 497  
 498  
 499  
 500  
 501  
 502  
 503  
 504  
 505  
 506  
 507  
 508  
 509  
 510  
 511  
 512  
 513  
 514  
 515  
 516  
 517  
 518  
 519  
 520  
 521  
 522  
 523  
 524  
 525

17/11/03

## VoIP Terminal Discovery Protocol

### Introduction

In deploying and provisioning a Voice over IP (VoIP) solution it is necessary to both configure the central PBX and the terminals. While each terminal can be individually provisioned it is often easier for an administrator to deploy unconfigured units and remotely provision them at a later time. With Symphony VoIP terminals this provisioning process can be achieved by remotely accessing the built in web based configuration. However before the built in web configuration can be accessed the IP address of the Symphony units must be determined. This document describes a mechanism for automatic network discovery of VoIP terminals and their IP addresses.

### Obtaining a network address

Before a terminal on the network can be accessed it needs to acquire a unique network address. DHCP (Dynamic Host Configuration Protocol) described in RFC1531 provides an industry standard method for dynamic allocation of IP addresses. Within DHCP addresses can be dynamically allocated or statically provisioned by the network administrator at the DHCP management console depending on the desired network topology. This allows address mappings to be easily redesigned from a central system. A single DHCP server can also serve more than one subnet by utilizing the BOOTP relay service provided by network routers.

Symphony VoIP terminals support automatic network address acquisition using DHCP. This gives plug and play benefits allowing an untrained user to simply plug-in the unit and have it network aware. Unfortunately on a device that does not have a display it is difficult to determine the IP address that the unit has acquired without administrative access to the DHCP server lease log. This document describes how this limitation can be removed.

### Automatic discovery

Automatic discovery can be achieved by use of an IP multicast group. On startup each VoIP terminal joins the VoIP-discovery multicast group and waits for a discovery message. When a user at an administrative console wishes to find the active VoIP terminals the console transmits a discovery message to the multicast group. Each terminal then responds with its information (IP address and MAC address) in a unicast packet back to the admin terminal.

In order to prevent a flood of messages the admin terminal can specify the following options in the discovery message:

- Time to respond. Each terminal will randomly choose a time between 0 and the specified time to respond before sending its response. This spreads out the messages and reduces the peak bandwidth required.
- Respond only if "on time" less than X. Each terminal will only respond if it has been powered up less than the specified "On time". This could be used by an admin terminal to hunt for recently installed units only (maybe poll every hour for units powered up within the hour).
- Time to live. This limits how many 'hops' the message will make through routers before being discarded. In normal operation a TTL of 1 will normally be used (ie. Restrict to local segment).

Use of a multicast group provides the most efficient way of reaching many sparsely distributed nodes. Unlike ethernet broadcasts which are received by all nodes on a segment, multicast is only received by nodes that are listening for the specific multicast group selected. In addition multicast messages are capable of being passed through routers so that the discovery can scan beyond the local subnet.

## Discovery packet

This packet is sent (UDP) to the multicast group to initiate discovery process. All values are sent in network order (big endian). A receiving node must be capable of ignoring any future extensions (ExtensionsPresent != 0) and correctly parsing the rest of the packet. A sending node will set an appropriate TTL for the multicast packet (TTL setting is network API dependant).

Offset	Size	Field Name	Description
0	WORD	Opcode	= 0x41 VOIP_DISCOVERY
2	WORD	Length	Length of entire packet
4	WORD	Checksum	Checksum of entire packet
6	OCTET	ExtensionsPresent	= 0x00 NO_EXTENSIONS_PRESENT
7	OCTET	ResponseTime	Time to respond. Each terminal will randomly choose a time between 0 and ResponseTime (in seconds) to respond before sending its response.
8	WORD	OnTime	Respond only if powered up less than OnTime (in seconds). A value of 0 means all respond.
10	WORD	ReportToPort	Port number to send response to
12	DWORD	ReportToIPAddress	IP address of node to send response to
16		...	(future extensions)

The checksum field is the 16 bit one's complement of the one's complement sum of all 16 bit words in the packet. For purposes of computing the checksum, the value of the checksum field is zero.

## Discovery Response packet

This packet is sent (UDP) unicast to the ReportTo address/port specified in the discovery process. A receiving node must be capable of ignoring any future extensions (ExtensionsPresent != 0) and correctly parsing the rest of the packet.

Offset	Size	Field Name	Description
0	WORD	Opcode	= 0x42 VOIP_DISCOVERY_RESPONSE
2	WORD	Length	Length of entire packet
4	WORD	Checksum	Checksum of entire packet
6	OCTET	ExtensionsPresent	= 0x00 NO_EXTENSIONS_PRESENT
7	OCTET	Reserved	(alignment/reserved for future use)
8	DWORD	ProtocolsSupported	Protocols supported (see table below)
12	DWORD	IPAddress	IP address of the responding node (will normally match the source IP address of the packet)

16	6 OCTETS	MacAddress	MAC address of the responding node
22	WORD	Reserved	(alignment/reserved for future use)
24		...	(future extensions)

ProtocolsSupported is a bit field with any of the following bits set. All other bit values are reserved for future allocation.

Protocol	Mask	Description
MGCP	0x00000001	MGCP supported
H323	0x00000002	H323 supported
HTTP	0x00000004	HTTP (web server) supported
SNMP	0x00000008	SNMP supported
TFTP	0x00000010	TFTP supported
(extension)	0x80000000	Reserved for indicating future extensions

### System requirements

The systems must meet the following requirements to be able to implement the mechanism described above:

- Administrative terminal must be able to transmit to a multicast group.
- VoIP terminal must be able to join a multicast group. This implies:
  - The ability to receive and filter multiple multicast mac addresses
  - Support of IGMP protocol to notify routers of multicast group membership
  -
- Network must support DHCP allocation of IP addresses

### Network numbers

Multicast group address	224.0.1.149 (assigned by IANA)
Multicast group port	4444

## DHCP Server

## Accessing configuration information

## Setting configuration parameters

```
String msg = new String("POST xxx.htm \r\ncontent-length:15\r\n\r\nSYSID=216ALPHA&\r\n");
```

```
InetAddress dest = InetAddress.getByName("207.82.37.216");
```

```
Socket s = new Socket(dest,80); // connect to webserver
```

```
OutputStream os = s.getOutputStream();
```

```
os.write(msg.getBytes());
```

## Reading configuration parameters

```
String msg = new String(
```

